

# MRS60/120 Programmable Charging Scale

Large Capacity, High Accuracy



## Technical Data

Model	MRS60	MRS120
Capacity	60 kg	120 kg
Resolution	4 g /0.2 oz / 0.01 lb	8 g /0.4 oz / 0.02 lb
Accuracy	0.05%	
Display Units	kg / oz / lb	
Operating Temperature	0 °C - 50 °C (32 °F - 122 °F)	
Storage Temperature	-10 °C - 60 °C (14 °F - 140 °F)	
Power Supply	3 * 3.7V Li-ion battery(18650,2400mAh)-Main body, 2 * 1.5V AAA-Wireless Controller	
Working Time	60 hours(full charge)	
Remark	Due to the strict transportation terms, we can not include any Li-ion battery and charger, you can buy from your local market.	
Accessories	M10 thread valve for refrigerant bottles	
Packing	Tool bag / Carton: 3 pcs	

# MRS10 Hydrocarbon Programmable Charging Scale

Professional Design, Accurate Charging



## Technical Data

Model	MRS10	MRS10K
Capacity	10 kg	
Resolution	1 g / 0.1 oz / 0.002 lb	
Accuracy	0.05%	
Display Units	kg / oz / lb	
Operating Temperature	0 °C - 50 °C (32 °F - 122 °F)	
Storage Temperature	-10 °C - 60 °C(14 °F - 140 °F)	
Power Supply	3*3.7V Li-ion battery (18650,2400mAh)	
Battery Life	60 hours (full charge)	
Remark	Due to the strict transportation terms, we can not include any Li-ion battery and charger, you can buy from your local market.	
Accessories	R290/600a Cylinder Adaptor (7/16"-20 UNF to 7/16"-28 UNEF Female)	R290/600a Cylinder Adaptor Single Valve Manifold , 2*45cm hose, Locking Plier(HL-1)
Packing	Tool bag / Carton: 5 pcs	Tool box / Cartons: 3 pcs