



智能真空泵 Intelligent Vacuum Pump

专利产品 PATENTED

特点 Feature

- ★无火花无刷电机适用于R1234YF,R290,R32等可燃制冷剂。
- ★外观新颖，更轻便。
- ★整体式缸体，气密性极高，质量更可靠。
- ★Sparkless brushless motor use for R1234YF,R290,R32 flammable refrigerants.
- ★Portable and novel appearance.
- ★Integrated cylinder,superior air impermeability.

单级智能真空泵 Single Stage Intelligent Vacuum Pump

型号 Item No.	WK-2S	WK-3S	WK-4S	WK-6S
速率 Flow Rate	2.5 CFM	3.5 CFM	4.5 CFM	6.5 CFM
	71 L/MIN	99 L/MIN	127 L/MIN	184 L/MIN
级数 Pole No.	单级 Single Stage	单级 Single Stage	单级 Single Stage	单级 Single Stage
极限真空 Ultimate Vac.	2 Pa	2 Pa	2 Pa	2 Pa
	60 microns	60 microns	60 microns	60 microns
功率 Power	1/4 HP	1/3 HP	1/3 HP	1/2 HP
接口 Inlet Port	1/4" & 3/8" flare	1/4" & 3/8" flare	1/4" & 3/8" flare	1/4" & 3/8" flare
泵油容量 Oil Capacity	340 ml	300 ml	300 ml	300 ml
外形尺寸 Dimension	267.5x130x265 mm	267.5x130x265 mm	267.5x130x265 mm	267.5x130x265 mm
净重 Weight	5.3 kgs	5.9 kgs	5.9 kgs	6.1 kgs

双级智能真空泵 Dual Stages Intelligent Vacuum Pump

型号 Item No.	WK-2BM	WK-3BM	WK-4BM
速率 Flow Rate	2.5 CFM	3.5 CFM	4.5 CFM
	71 L/MIN	99 L/MIN	127 L/MIN
级数 Pole No.	双级 Dual Stages	双级 Dual Stages	双级 Dual Stages
极限真空 Ultimate Vac.	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa
	15 microns	15 microns	15 microns
功率 Power	1/4 HP	1/3 HP	1/2 HP
接口 Inlet Port	1/4" & 3/8" flare	1/4" & 3/8" flare	1/4" & 3/8" flare
泵油容量 Oil Capacity	320 ml	300 ml	300 ml
外形尺寸 Dimension	296x130x265 mm	315x136x312mm	315x136x312mm
净重 Weight	6 kgs	6 kgs	7 kgs



WK-8iBM

智能真空泵 Intelligent Vacuum Pump

专利产品 PATENTED



▲便携背带 Portable Straps

特点 Feature

- ★采用全程真空计 ATM~0.1 Pa。
- ★达到设定目标真空压力后背光闪烁提醒。
- ★无火花无刷电机适用于R1234YF, R290, R32等可燃制冷剂。
- ★外观新颖，更轻便。
- ★整体式缸体，气密性极高，质量更可靠。
- ★Whole pressure range vacuum meter ATM~0.1 Pa.
- ★Backlight blinking when target pressure reached.
- ★Sparkless brushless motor use for R1234YF, R290, R32 etc flammable refrigerants.
- ★Portable and novel appearance.
- ★Integrated cylinder, superior air impermeability.

智能真空泵(真空计型) Intelligent Vacuum Pump(Vacuum Meter)

型号 Item No.	WK-8Si	WK-10Si	WK-12Si	WK-6iBM	WK-8iBM	WK-10iBM	WK-12iBM
速率 Flow Rate	8.5 CFM	10.5 CFM	12.5 CFM	6.5 CFM	8.5 CFM	10.5 CFM	12.5 CFM
	241 L/MIN	297 L/MIN	354 L/MIN	184 L/MIN	241 L/MIN	297 L/MIN	354 L/MIN
级数 Pole No.	单级 Single Stage	单级 Single Stage	单级 Single Stage	双级 Dual Stages	双级 Dual Stages	双级 Dual Stages	双级 Dual Stages
极限真空 Ultimate Vac.	2 Pa	2 Pa	2 Pa	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa
	60 microns	60 microns	60 microns	15 microns	15 microns	15 microns	15 microns
功率 Power	1HP	1HP	1HP	1HP	1HP	1HP	1HP
接口 Inlet Port	1/4" & 3/8" flare	1/4" & 3/8" flare	1/4" & 3/8" flare	1/4" & 3/8" flare	1/4" & 3/8" flare	1/4" & 3/8" flare	1/4" & 3/8" flare
泵油容量 Oil Capacity	600 ml	600 ml	600 ml	550 ml	550ml	600 ml	600 ml
外形尺寸 Dimension	315x136x312mm	315x136x312mm	315x136x312mm	352x136x312mm	352x136x312mm	352x136x312mm	352x136x312mm
净重 Weight	11 kgs	11 kgs	11 kgs	11.5 kgs	11.5 kgs	11.5 kgs	11.5 kgs